



ICE MACHINE SOLUTIONS

Roughly 70% of service calls on ice machines are water related. The most frequent water related problem associated with ice machines is lime scale accumulation.

Effective water filtration solves the following:

- Chlorine taste and odor is removed reducing potential corrosion issues.
- Mineral scale build up responsible for increased maintenance is reduced.
- Sediment that causes cloudy ice and plugs distribution tubes and float valves is removed.
- Energy efficiency and machine life are increased while reducing costly service calls.

Sizing Guidelines

For correct system sizing, please refer to the water flow requirements of the ice machine. Water flow requirements will vary from one manufacturer to the next on the same sized machine. The following guidelines are based on average water pressure and water quality. Variations in water quality or pressure may reduce overall water flow especially as filters are in service for prolonged periods.

IceSpec™ filters provide excellent sediment filtration, chlorine removal and mineral scale control. The gallon capacity ratings of the filters are based solely on chlorine removal and not scale control. **Recommended filter change interval is 6 months based on the useful life of the scale control component.**

IceSpec System:	Item #:	Service Flow Rate:	Rated Capacity:	Machine Size Cuber:	Machine Size Flaker:	Conn Size:	System Dimensions:	Ship Weight:
IS 10 Single	310010	1.65 GPM	10,000	<350lbs/day	<1,000lbs/day	3/8	4x15x4	4lbs
IS 16 Single	310011	2.00 GPM	15,000	<500lbs/day	<1,500lbs/day	3/8	4x21x4	5lbs
IS 10 Twin	310012	3.30 GPM	20,000	<800lbs/day	<2,000lbs/day	1/2	15x19x5.5	7lbs
IS 16 Twin	310013	4.00 GPM	30,000	<1,000lbs/day	<2,500lbs/day	1/2	15x26x5.5	9lbs
IS 10 Triple	310014	5.00 GPM	30,000	<1,300lbs/day	<3,000lbs/day	1/2	19x19x5	10lbs
IS 16 Triple	310015	6.00 GPM	45,000	<1,800lbs/day	<3,500lbs/day	1/2	19x26x5	13lbs
IS 10 Quad	310016	6.65 GPM	40,000	<2,000lbs/day		1/2	23x19x5	12lbs
IS 16 Quad	310017	8.00 GPM	60,000	<2,400lbs/day		1/2	23x26x5	16lbs

- Patented HydroBlend™ insert provides optimum scale prevention.
- Compact design facilitates system placement and installation.
- Bayonet Style Quick Disconnect cartridge makes filter replacement quick & easy.

IS 10 Single



IS 10 Twin



IS 16 Single



IS 16 Triple

